

# Style – Tables

## Default styles

For basic styling—light padding and only horizontal dividers—add the base class `.table` to any `<table>`.

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

```
<table>
  ...
</table>
```

---

## Optional classes

Add any of the following classes to the `.table` base class.

### `.table-striped`

Adds zebra-striping to any table row within the `<tbody>` via the `:nth-child` CSS selector (not available in IE7-IE8).

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

```
<table>
  ...
```

```
</table>
```

## **.table-bordered**

Add borders and rounded corners to the table.

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
	Mark	Otto	@TwBootstrap
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

```
<table>
```

```
...
```

```
</table>
```

## **.table-hover**

Enable a hover state on table rows within a `<tbody>`.

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry the Bird		@twitter

```
<table>
```

```
...
```

```
</table>
```

## **.table-condensed**

Makes tables more compact by cutting cell padding in half.

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat

#	First Name	Last Name	Username
3	Larry	the Bird	@twitter

```
<table>
...
</table>
```

---

## Optional row classes

Use contextual classes to color table rows.

Class	Description
.success	Indicates a successful or positive action.
.error	Indicates a dangerous or potentially negative action.
.warning	Indicates a warning that might need attention.
.info	Used as an alternative to the default styles.

#	Product	Payment Taken	Status
1	TB – Monthly	01/04/2012	Approved
2	TB – Monthly	02/04/2012	Declined
3	TB – Monthly	03/04/2012	Pending
4	TB – Monthly	04/04/2012	Call in to confirm

```
...
<tr class="success">
  <td>1</td>
  <td>TB - Monthly</td>
  <td>01/04/2012</td>
  <td>Approved</td>
</tr>
...
```

---

# Supported table markup

List of supported table HTML elements and how they should be used.

Tag	Description
<code>&lt;table&gt;</code>	Wrapping element for displaying data in a tabular format
<code>&lt;thead&gt;</code>	Container element for table header rows ( <code>&lt;tr&gt;</code> ) to label table columns
<code>&lt;tbody&gt;</code>	Container element for table rows ( <code>&lt;tr&gt;</code> ) in the body of the table
<code>&lt;tr&gt;</code>	Container element for a set of table cells ( <code>&lt;td&gt;</code> or <code>&lt;th&gt;</code> ) that appears on a single row
<code>&lt;td&gt;</code>	Default table cell
<code>&lt;th&gt;</code>	Special table cell for column (or row, depending on scope and placement) labels. Must be used within a <code>&lt;thead&gt;</code>
<code>&lt;caption&gt;</code>	Description or summary of what the table holds, especially useful for screen readers

```
<table>
  <caption>...</caption>
  <thead>
    <tr>
      <th>...</th>
      <th>...</th>
    </tr>
  </thead>
  <tbody>
    <tr>
      <td>...</td>
      <td>...</td>
    </tr>
```

```
</tbody>  
</table>
```